PRE-CONSTRUCTION

- · HIA fixed site works.
- · Plans Specifications.
- · Engineers soil report & slab design.
- · Council building application fees

SITE WORKS FOUNDATIONS & CONNECTIONS

- Site scrape and/or balanced cut & fill excavation for up to 1500mm site fall over the building platform.
- Engineer designed concrete slab to suit up to "H2" slab with bulk concrete piering (up to and including a depth of 600mm).
- Termite treatment to slab penetrations and physical perimeter barrier.
- Sewer & storm water connections to existing serviceable connection points for sites up to 600m2 in size with a standard.
- 6 meter set back from front boundary (battleaxe, other odd shaped blocks and blocks where service connection exceeds standard allowances may incur extra service costs).
- Eight (8) meters plan length of electrical mains.
- Water connection from pre-tapped water main up to and including six (6) meter setback to house.
- House constructed for "N2" wind rating conditions (W33).
- · No allowance is made for retaining walls.

ENERGY EFFICIENCY

- Bulk ceiling insulation rating R2.5 to ceiling area.
- Double sided foil wall-wrap to external stud walls.
- Energy efficient aluminium improved windows and sliding door units
- · Weather stripping to hinged external doors.
- · Electric hot water system.
- 500 KPA water pressure limiting device.

- · LED down-lights.
- · Approximately 1.8kw solar power system.

BRICKS, WINDOWS, ROOF AND GARAGE

- Colorbond roof.
- Colorbond fascia & gutter from the standard builders' range of colours.
- Select range of clay bricks from the builder's standard range.
- · Off white mortar.
- Powder coated aluminium windows from the standard builders' range of colours, with obscure glass to wet areas.
- Keyed window locks to all opening sashes and sliding doors.
- Auto Sectional garage door to garage from the standard builders' range of colours and two (2) handsets.

KITCHEN INCLUSIONS

- · 20mm manufactured stone bench top.
- Soft close cabinetry to cupboards.
- Laminate finish cupboards from the standard builder's range of laminates.
- Door handles from the standard builder's range.
- Laminate finish microwave oven provision to cabinetry.
- · 600mm under-bench oven.
- · Electric ceramic 600mm cooktop.
- · Freestanding stainless-steel dishwasher.
- · Stainless steel 600mm slide-out rangehood.
- 13/4 bowl stainless steel kitchen sink.
- · Chrome sink mixer.
- Cold water point to fridge space for an ice maker.
- · Bulkhead above kitchen overhead cupboards.

BATHROOM ENSUITE AND TOILETS

· Wall-hung vanities with laminate bench

tops from the standard builder's range of laminates.

- · Soft close cabinetry to cupboards.
- Door handles from the standard builder's range.
- Clear laminated glass shower screens with powder coated aluminium frames from the standard builder's range of colours.
- · White acrylic bath.
- 900mm high polished edge mirrors fitted to the same width as the vanity unit.
- Chrome mixer tapware, double towel rails and toilet roll holders.
- · Vitreous China close coupled toilet suites.
- Semi-inset basins (or semi recessed as required).
- Shower on rail to bathroom and ensuite showers.

CERAMIC TILING

- · Bathroom & ensuite floors, and:
 - 2000mm high to showers
 - 500mm above bath (nominal)
 - 200mm skirting tile.
- · Kitchen tiled splashback:
 - 600mm high off bench.
- · Toilet & Laundry floors, and:
 - 400mm splash back over tub
 - 200mm skirting tiles
- No allowance has been made for frieze or decorator tiles.
- No allowance has been made for laying of border tiles, 45-degree patterns or floor feature tile layouts.

ELECTRICAL

- · Earth leakage safety switch & circuit breakers.
- Single phase underground power connection from existing supply point.
- Meter box will be installed on the side nearest to the mains connection point.
- · One (1) double power point to each room and

- as per electrical plan.
- One (1) 240-volt downlight point to each room as per electrical plan.
- · Two (2) external paraflood light points.
- • Two (2) television points complete with 5 lineal meters of cable and no antenna.
- · Smoke detectors hard wired with battery backup.
- · Pre-wiring for two (2) Telstra phone points.
- · Exhaust fan to bathroom and ensuite.
- Single GPO to microwave oven provision in kitchen.
- USB/double power point to the end of kitchen cabinetry.

STANDARD INTERNAL AND EXTERNAL FEA-TURES

- 2550mm ceiling heights throughout (ground level only in 2 storey homes).
- Round aluminium powder-coated handrail and vertical balustrade to external balcony as selected from builders' standard range where applicable.
- · Paint grade front door with clear glazing.
- Paint grade hinged doors to other external doors if applicable.
- · Paint grade flush panel internal passage doors.
- Magnetic door stops from builders' standard range to passage doors.
- Vinyl sliders from builders' standard range to wardrobe doors.
- · Builders range exterior leverset to front door
- · Interior leverset to internal doors.
- · 90mm paint grade coved cornice.
- · 41mm paint grade splayed architraves.
- · 67mm paint grade splayed skirting.
- · Paint:
 - Three (3) coat internal paint system 2 colours allowed i.e. 1 colour to wall and 1 colour to timber work,
 - Two (2) coats to ceiling to Paint Manufacturers standard specifications,

- Two (2) coat external paint system to external trim and doors to paint manufacturers standard specifications.
- · 45 ltr laundry trough and cabinet.
- · Two (2) external garden hose taps.
- AAA rated water saving shower heads and tapware.
- Internal & external builders house clean and site clean after construction.
- Carpet grade staircase with painted timber balustrade for staircases as selected from builders' standard range.

WARRANTIES

- · 6-month maintenance period
- · Statutory structural guarantee period

TURN KEY PACKAGE

PRE-CONSTRUCTION

 Provide additional council cross over and building application fees according to local city council.

SITE WORKS

 Provide additional driveway cut and excavation including kerb cut-out and removal when non-mountable kerb exists.

WINDOWS

- · Powder coated aluminium fly screens.
- · Powder coated frames to glass sliding doors.
- · Powder coated frames to opening windows.

LANDSCAPING

- Provide up to 70 lineal meters of 1800mm high Colorbond fencing.
- · Provide (1) Colorbond gate.
- Provide up to 60m2 of broom finished coloured concrete driveway, front path and porch.
- · Provide up to 300 m2 of A-Grade turf.
- Provide one (1) 15m2 garden bed including clay paver edge, builders' range plants and mulch.

INTERNAL & EXTERNAL FEATURES

- Provide carpet to all bedrooms and living rooms as selected from the builders' standard range.
- Provide main floor tiles to all other internal areas (excluding garage).
- Provide suitable external grade tile finish to alfresco slab as selected from the builders' standard range.
- Provide a fold down wall mounted clothes line as selected from the builders' standard range.
- Provide a TV antenna and booster (as required) to roof as selected from the builders' standard range.
- Provide a letter box as selected from builders' standard range.
- Provide Roller blinds throughout. (Excluding Wet rooms)
- Provide (1) white fan/light to all bedrooms.
- Provide (1) split system A/C from builders' standard range to living room and (1) to master bedroom.
- Provide internal & external builders house clean.
- Povide up to 60m2 of broom finished coloured concrete driveway, front path and porch.