



The key intent of the Design Guidelines is to ensure that future development respects the landscape significance of the site, while ensuring that the interface between residential lots and the public realm is managed appropriately.

The objectives are outlined as follows:

- To create a sense of place where the community can enjoy a safe and relaxed lifestyle
- To create a pedestrian orientated environment
- Ensure a good outcome particularly in this established attractive area and protecting home investments by promoting quality design;
- Provide guidance to appropriate built form so that it does not cause detriment to the scenic landscape and street scape environment;
- Ensure sufficient front and rear setbacks to provide space for new landscaping and create a consistent sense of character through siting.

Design guidelines Glanmire Park



BUILT FORM

Objective

To discourage visually bulky and obtrusive dwellings and promote high quality architectural design.

Requirements

- R1 Buildings should meet Clause 54 of the Moira Planning scheme in addition to these guidelines.
- R2 The entry to the home must be visible from the street.
- Passive surveillance should be provided to streets with use of at least one habitable window facing the street scape.
- R4 Built form should not exceed 9m in height and two storeys.
- R5 Garages are to be designed and sited to ensure that they are not dominant upon the street frontage.
- R6 Carports are permitted provided they are located within the side or rear setbacks and are minimally visible from the streetscape.
- R7 Outbuildings for storage must be located to the rear of the dwelling and must not be viewable from the street scape.
- R8 Outbuildings should be chosen in subdued Colorbond® colours to complement the dwellings.

Built Form DESIGN GUIDELINES GLANMIRE PARK



FAÇADE ARTICULATION

Objective

To ensure buildings contribute positively to the street scape by using a variety of external finishes and creating interesting and highly articulated façades.

Requirements

- R1 Two dwellings with the same façade shall not be built within 5 house lots of the original lot
- R2 Dwellings must include a covered porch of a minimum 1.5m in depth.
- R3 Colours and materials should comprise of subdued earthy tones that are reflective of the natural surrounds.

Façade Articulation | DESIGN GUIDELINES | GLANMIRE PARK



ROOF LINES

Objective

To ensure roof designs are complimentary to the street scape, are contemporary in nature and do not dominate the skyline.

Requirements

- R1 Roof materials may be constructed in Colorbond® roof sheeting or an approved tile material, to embody contemporary Australian design.
- R2 Roofs should be pitched at a minimum 20 degrees.
- Pitched roofs, with the exception of walls on boundaries or facing south, require extended eaves at a minimum 450mm except where parapet walls are provided.
- R4 The use of skillion roofs are permitted at a minimum of 15 degrees with a minimum of two roof planes.
- R5 Parapet walls are encouraged to utilise shading structures above windows if facing north or west for sun protection but must not exceed more than 50% of any façade.
- R6 Air conditioning/Evaporative cooling units mounted on roofs, antennas and satellites should not be visible at the street interface.

Rooflines DESIGN GUIDELINES GLANMIRE PARK



DRIVEWAYS & PATHS

Objective

 $\label{toincrease} To increase permeable areas and maintain space for landscaping to soften hard surfaces.$

Requirements

- R1 A maximum of one crossover per lot is permitted.
- P2 Driveways must be a minimum of 3m wide and upon entry maintain setbacks to side boundaries of at least 0.5m to allow space for landscaping.
- R3 Pedestrian paths of permeable materials should be incorporated in the landscape plans to provide formal access to the dwelling entrance.
- R4 Driveways should be constructed in concrete or permeable pavement systems. The latter is preferable to allow water infiltration into plant root zones.

Driveways & Paths DESIGN GUIDELINES GLANMIRE PARK



BUILDING MATERIALS

Objective

To ensure materials are complimentary, varied and representative of contemporary architectural design.

Requirements

- R1 Façades must incorporate at least two aesthetic building materials.
- R2 Any one material should only cover a maximum of 70% of the building façade.
- R3 Garage door materials should be horizontal timber boarding, grooved ply or muted coloured metal cladding representative of timber boards.
- R4 Outbuildings should be chosen in subdued Colorbond® colours to complement the dwellings

Suggested Materials

- Brick veneer in an approved colour (no more than two muted tones, no heritage colours);
- Rendered masonry painted in stripped back tones;
- Lightweight materials such as weatherboard or feature timber cladding;
- **\$** Stonework; and
- Painted precast fibre cement cladding.

Building Materials DESIGN GUIDELINES GLANMIRE PARK

COLORBOND® PALETTE



COLORBOND® Steel Colours



SETBACKS

Objective

To produce a pattern of spacious areas between dwellings and maintain areas for landscaping.

Requirements

- R1 Front setbacks must not be less than 5m to the front facade of the dwelling.
- R2 Porches can enter the front setback in accordance with the requirements of clause 54 of the Moira Planning Scheme.
- R3 Side setbacks are permitted to be 'zero' along one boundary, in accordance with the requirements of Clause 54 of the Moira Planning Scheme and must provide a least 1m on the opposite side. A minimum of 2m down one side boundary is preferable.
- R4 Rear setbacks must not be less than 3m to ensure that space for landscaping is maintained. Permeable structures such as pergolas or terraces can encroach on this setback.

Setbacks DESIGN GUIDELINES GLANMIRE PARK



FENCING

Objective

To facilitate an openness of frontages and permeability with vegetation to create a social environment and contribute to passive surveillance of the street.

The detail of all fencing is to be submitted with plans for approval.

Requirements

- R1 Front fences are discouraged. If a front fence is desired, the maximum height allowed will be 1.2m, have a minimum of 60% transparency and should reflect the semi rural character, such as low post and rail
- R2 Fencing between lots are to be 1.8m in height and clad with Woodland Grey Colorbond[®]. On a corner lot this may partially face the streetscape.

Front Fencing DESIGN GUIDELINES GLANMIRE PARK



LANDSCAPING

Objective

To contribute to the attractiveness of the development and the visual quality of the street, as well as to provide a sustainable vegetated and attractive leafy setting for each home.

Requirements

- R1 At least 40% of the front garden must be landscaped using trees, shrubs, tufting plants, ground covers or lawn.
- R2 Landscape works for the front yard should occur within 6 months of the date of issue of the occupancy permit for each home.

This time frame allows for planting when the weather is less harsh

for plants to establish and should be taken into consideration.

- R3 A specified mature deciduous tree must be planted between the front façade of the home and the front street as per the Glanmire Park Landscape Master Plan.
- R4 Where appropriate, the use of drought tolerant and predominantly native species is encouraged.
- R5 Lots that contain retained trees must not be removed, destroyed, lopped or inflicted damage upon to said trees unless deemed hazardous by a qualified arborist and written consent is given by the Responsible Authority.

Landscaping DESIGN GUIDELINES GLANMIRE PARK



TURNKEY OPTIONS





Colour on Concrete Paving

Driveway (up to 30m²).



Fencing

Full share fencing to sides and rear boundaries (note fence finishes inline with front facade on one side and butts up to the rear of the garage on the other side). 1800mm high, all Colorbond® or timber paling with timber capped 125 x 75mm exposed posts (estate compliant).



Wing Fence

1800mm high and 900mm wide gate to side of house (if required). Fencing type allowed Colorbond® / timber paling capped with 125 x 75mm exposed posts.



Front Landscaping

includes mixture of mulch, pebbles, rocks, garden bed with 150mm plants, dripper system, battery operated timer, 2 of 1200mm high trees to front of dwelling and concrete letterbox to suit style of home.



Rear Landscaping

Includes mulched garden bed with trees and / or plants to rear boundary, $12m^2$ of instant natural turf, topping to remainder of land to rear and side boundaries, dripper system connected to tap, fold away clothes line with $3m^2$ of colour on concrete pad and $12m^2$ of colour on concrete paving to rear or alfresco area (plan specific).



TV Antennae

Connection to roof including connection to internal TV points.



Split System Air Conditioner

(3.3kw) including isolation switch and condenser to be wall mounted. Note- installation price includes condenser and head unit to be installed to an external wall within 3m of each other.



Alarm System

Comes with 3 sensors including panel to walk in robe and key pad to entrance including single power point.



Reconstituted Stone

Benchtops to kitchen in lieu of standard laminate max length 3000×800 island and 3000×600 rear including 20mm square edge, installation to cupboards.



Holland Blinds

Comes with metal chain and Vibe Block out (design specific).



Flyscreens

Aluminium framed to all openable windows - colour to match window colour.

The builder reserves the right to substitute the make, model or type of any of the above products to maintain the quality and product development of its homes. Changes may be made subject to Res Code requirements. Window and sliding door sizes may vary subject to energy rating requirements.

Effective date: 01.05.2024

HOMES SPECIFICATIONS

Kitchen Appliances

Over

Stainless steel 600mm fan forced oven.

Hot Plate

Stainless steel 600mm gas cook top with wok burner.

Rangehood

Stainless steel 600mm wide canopy range hood.

Dishwasher

Stainless steel dishwasher.

Sink

Double bowl stainless steel sink.

Tap

Flickmaster tap, chrome finish.

Cabinetry

Cupboards

Fully lined melamine modular cabinets including overhead cupboards and cupboards above refrigerator space as per working drawings. Laminate finish doors from builder's range Category 1.

Doors/Drawers

Standard laminate from builder's predetermined colour boards.

Microwave Provision

Standard laminate including single power point.

Kitchen Bench Top

Laminate square edge from builder's predetermined colour boards.

Vanity Bench Tops

850mm high laminate square edge benchtop from builder's predetermined colour boards.

Handles

Selected from builder's predetermined colour boards.

Bathroom & Ensuite

Basins

Vitreous china vanity basin (white).

Mirrors

1150mm high polished edge mirror to full width of vanity.

Bath

Vega 1500mm freestanding bath (white). Product Specific.

Shower Bases

Tiled shower bases with waterproof system throughout.

Shower Screens

Step free tiled shower bases with waterproof system throughout. (Product Specific)

Taps

Chrome mixer tapware.

Shower Outlet

Handheld shower, rail and slider in chrome finish to ensuite and bathroom.

Toilet Suite

Vitreous china, close coupled toilet suite in white with soft close top.

Accessories

600 mm single towel rail or 2 no. hooks and toilet roll holders in chrome finish.

Exhaust Fans

Exhaust fans vented to outside air via a duct.

Ceramic Tiling

Wall Tiles

Wall tiles to kitchen, bathroom, ensuite and laundry where shown on plans. Tile selection as per builder's predetermined colour boards.

Floor Tiles

Floor tiles to ensuite, bathroom, laundry and WC. selection as per builder's predetermined colour boards.

Floor Coverings

Laminate Flooring

Builders range laminated flooring as shown on plan. Selection as per builder's predetermined colour boards.

Carpet

Carpet to area's not tiled or with laminate flooring. Selections as per builders predetermined colour boards and as shown on plan.

Paint - 2 Coat Application

Timberwork

Gloss enamel to internal doors, jambs & mouldings.

Ceilings

Flat acrylic to ceilings.

Internal Walls

Washable low sheen acrylic to internal walls.

Entry Door

Gloss enamel to front entry door.

Colours

Colours selected as per builder's predetermined colour boards.

Staircase (double storey homes)

Pine closed stringers, with MDF treads and risers with carpet cover. Pine No.8 wall rail. (dwarf walls by AHB). No balustrade.

External Features

Bricks

Clay brick selection from builders' pre-determined colour boards to single storey homes and ground floor of double storey homes.

Mortar Joints

Face Brickwork - Natural colour rolled joints.

Light Weight Cladding

Rendered lightweight foam to single and double storey facades including first floor of double storey facades. Finish and colour to be selected from builder's pre-determined colour boards (design specific – refer to working drawings for extent of cover).

Front Elevations

As per Working Drawings. Acrylic render to selected areas as per plan (Product Specific).

Windows and Doors:

Single Storey Homes

Feature aluminium windows to front elevation (Product Specific). Sliding aluminium windows to sides and rear.

Double glazed awning windows and sliding doors as required to meet 7-star energy rating. Aluminium improved windows throughout.

Double Storey Homes

Double glazed awning windows and sliding doors throughout as required to meet 7 star energy rating.

Entry Frame

Aluminium, powder coat finish (Product Specific). Clear glazed sidelight(s) to double storey homes (design specific).

Front Entry Door

2040mm high feature front door as per facade.

Door Furniture

Front Door: Entrance lockset in polished stainless steel with deadbolt. (Product Specific).

Ext. Hinged Door

Entrance lockset in polished stainless steel to external door.

Infill Over Windows

Brick infills over all windows and doors (excluding garage front elevation) to single storey homes and ground floor only of double storey homes.

Door Seal

Door seal and weather seal to all external hinged doors.

Balcony Balustrade

Facade Specific

Balcony Tiling

Builders range external ceramic tile.

Insulation

Ceiling

Ceiling insulation as required to meet 7 star energy rating (excludes garage ceiling).

Walls

Wall insulation including sisalation to external brick veneer walls (excluding garage) and wall between garage and house as required to meet 7 star energy rating.

Garage

General

Garage with tiled roof including Colorbond® sectional overhead door with remote control, rendered lightweight foam over garage door, plaster ceiling and concrete floor.

External Walls

Brick veneer.

Pedestrian Door

Weatherproof flush panel door, low sheen acrylic paint finish. (Product Specific).

Door Frame

Aluminium powder coat finish.

Door Furniture

Entrance lockset.

Internal Features

Doors

2040mm high flush panel hinged or sliding doors (house design specific).

Door Furniture

Lever door furniture in polished chrome finish to all rooms.

Mouldings

 67×18 mm Beveled MDF skirting & 67×18 mm MDF beveled architraves.

Door Stops

Plastic white door stops to hinged doors (where applicable).

Door Seals

Door seal to nominated internal doors.

Note: This will be in accordance with energy rating assessor's report.

Hot Water System (Estate Specific)

Hot Water

Air-water heat pump system with 170 litre storage tank, and continuous mains pressure 20 litre gas booster.

OF

Gas continuous flow water heater system (up to $27 \, \text{sq.'s} - 20 \, \text{L/M}$ Unit & $28 \, \text{sq.'s}$ and above $26 \, \text{L/M}$ unit). Note: Continuous flow water heater will be used in estates where recycled water is available.

Laundry

Trough

Stainless steel tub and melamine cupboard with bypass.

Taj

Flickmaster tap, chrome finish.

Washing Machine

Chrome washing machine stops/grubs.

Plaster

Plasterwork

10mm plasterboard to ceiling and wall, water resistant plaster to ensuite, bathroom, above laundry trough including 75mm cove cornice throughout.

Plumbing

Taps

2 No. external taps.

(1 to front water meter and 1 next to laundry door). Product Specific.

Roofing

Pitch

Roof pitch to be 22.5 degrees.

Material

Dark colour on roof tiles from builder's predetermined colour boards to meet 7 star energy rating.

Fascia & Guttering

Colorbond® fascia, guttering and downpipes.

Heating

Heating

Gas ducted heating to bedrooms and living areas, (excludes 'wet areas'). Total number of points and unit size product specific.

Framing

Framing

Engineered pine wall frame and roof trusses.

Storage

Shelving

Walk In Robe: One white melamine shelf with single hanging rail.

Rohe

One white melamine shelf with single hanging rail.

Pantry/Linen

Four white melamine shelves.

Doors

Robes: 2040mm high readicote flush panel hinged or sliding doors as per plan.

Pantry/Linen

2040mm high readicote flush panel, hinged door(s).

Handles

Handles in polished chrome finish.

Ceilings

Height

2440mm (nominal) height throughout.

Electrical

Solar PV

Solar PV (Photovoltaic) System 2.5kW.

Internal Light Points

100mm diameter 240V downlights fittings (colour – white) throughout as per standard electrical layout (supply/install light globes to all light fittings in the home).

External Lights

100mm diameter fixed 240V white recessed downlight to front entry and alfresco where applicable. Weather proof Para flood light to rear as per drawings.

Power Points

Double power points throughout excluding dishwasher, microwave and refrigerator provision (refer working electrical plan).

TV Points

Two points including 5 metres of coaxial cable to roof space (one to main bedroom and one to living area).

Telephone Point

Two pre-wired telephone points to kitchen & Master Bedroom with wall plate as per working drawings including connection availability to the National Broadband Network (NBN) - *basic pack only.*

Switch Plates

White wall mounted switches.

Smoke Detector(s)

Hardwired with battery backup.

Safety Switches

RCD safety switch and circuit breakers to meter box.

Site Conditions / Foundations

Foundation Class

Up to Class H2 concrete slab with fall of land up to 500mm across the length and/or width of the allotment. Excludes concrete bored piers due to existing uncontrolled fill being placed on the allotment. If fill is shown on allotment, a lot specific level 1 compaction report is required or additional charges may apply.

Temporary Fencing

Supply and hire of temporary fencing to site where required to council requirements.

Silt Fence

Supply and hire of environmental silt fence to front of property as required by council.

Rock Allowance

Allowance of rock excavation and removal (If explosives or core drilling required, extra charge will apply).

Termite Treatment

Termite spray system where required by relevant authority.

Angle of Repose

Home to be sited a minimum of three metres from easement. (If sited closer then additional charges may apply).

Structural

Warranty

10 year structural warranty and 3 month maintenance warranty

Service Connections

Connections are based on an allotment of up to 650 square metres with a maximum six metre setback to house (connection to stormwater and sewer points are provide within the building lot, single phase underground power up to 12 metres from pit and same side dry water tapping). Does not included electricity and telephone consumer account opening fees.

NBN basic, cable, telephone points / 1 of data point, NBN conduit and connection point. BAL 12.5 - will be included FREE if required. Recycled Water – will be included FREE if required.

7 Star Energy

Minimum 7 star energy rating for standard house plans including all facades on any orientation. Based on Ballarat climate zone and like for like dwellings either side.

INCLUSIONS RANGE

Bathroom



Phoenix Sonata hand shower & rail in chrome



Executive shower screen tiled base



Towel rail & toilet roll holder



White acrylic bath



Shower Mixer in chrome



Ceramic basin - white



Toilet suite with soft close seat in white



Basin Mixer in chrome

Laundry & Hot Water Service



Laminated white cabinet with 45 litre stainless steel trough



Air-water heat pump hot water system with 170 litre storage tank, and continuous mains pressure gas booster (estate specific)





Gas continuous flow water heater system (estate specific. Will be used in estates where recycled water is available.)

INCLUSIONS RANGE

Kitchen & Flooring



Double bowl sink



600mm dishwasher 12 settings, 7 programs



600mm electric fan forced inbuilt oven with manual timer



600mm canopy range hood



Benchtop (Laminate)



600mm cooktop 4 burner w/wok cast iron trivets



Sink Mixer - Chrome



Bolero timber look laminate flooring

Garage & Roofing



Remote controlled Colorbond® Sectional overhead garage door with 2 remotes



Monier Atura roof tile

The builder reserves the right to substitute the make, model or type of any of the above products to maintain the quality and product development of its homes. Changes maybe made subject to Res Code requirements. Imagery for illustrative purposes only.

CLASSIC

(Included)











Garage Door
Surfmist



5.
Roof Tiles
Salt Spray









CLASSIC

(Included)

EXTERNAL COLOURS - OLYMPIA





1. Brickwork Bark



2. Render 1 Wallaby



3. Render 2 Dune



4.
Garage Door
Monument



Sambuca



6. Gutters Night Sky



7. Fascias Night Sky



8.
Front Entry Door
Wallaby



CLASSIC

(Included)

EXTERNAL COLOURS - SAHARA















Roof Tiles Barramundi



6. **Gutters** Monument



7. Fascias Monument



Front Entry Door Monument



CLASSIC (Included)











Garage Door Monument



Roof Tiles Barramundi



6. **Gutters** Monument



7. Fascias Monument



Front Entry Door Monument













4.
Garage Door
Timberlook
Blushed Teak



5.
Roof Tiles
Sambuca



6. Gutters Night Sky



7. Fascias Night Sky



8.
Front Entry Door
Wallaby













3.
Render 2
Charcol



4.
Garage Door
Timberlook
Ashen Black Oak



5.
Roof Tiles
Sambuca



6. Gutters Night Sky



7. Fascias Night Sky



8.
Front Entry Door
Black



INTERNAL COLOURS - CASHMERE

1. **Splashback**United Ice Grey

2. Overhead cupboards
Idyllic

3. Base cupboards Seal Grey

4. Kitchen BenchtopPure Marble





5. Laminate flooringMaize

6. Carpet Rainstorm

7. Floor tiles Belga Grey

8. Cupboards Idyllic

9. Vanity benchtopPure Marble



Disclaimer:

Images provided are for illustration purpose only. The builder reserves the right to substitute the make, model or type of any of the above products to maintain the quality and product development of its homes. Changes may be made subject to Res-Code requirements. Window and sliding door sizes may vary subject to energy rating requirements.

INTERNAL COLOURS - CLOUDBURST

Splashback
 United White

2. Overhead cupboards
Autumn Oak

3. Base cupboardsCrystal White

4. Kitchen BenchtopPure Marble





5. Laminate flooring
Rustic Oatmeal

6. Carpet Vintage Pewter

7. Floor tiles Belga White

8. Cupboards Autumn Oak

9. Vanity benchtopPure Marble

Disclaimer:

Images provided are for illustration purpose only. The builder reserves the right to substitute the make, model or type of any of the above products to maintain the quality and product development of its homes. Changes may be made subject to Res-Code requirements. Window and sliding door sizes may vary subject to energy rating requirements.

INTERNAL COLOURS - TEMPO

1. Splashback United Ice Grey

2. Overhead cupboards Silver Riftwood


3. Base cupboards Crystal White

4. Kitchen Benchtop Pure Marble










7. Floor tiles Warehouse Dark

> 8. Cupboards Seal Grey

9. Vanity benchtop





Images provided are for illustration purpose only. The builder reserves the right to substitute the make, model or type of any of the above products to maintain the quality and product development of its homes. Changes may be made subject to Res-Code requirements. Window and sliding door sizes may vary subject to energy rating requirements.